

PT1 v2 Payment Terminal



PT1 v2

Payment Terminal

- ✓ Account Card authorisation
- ✓ Credit Card authorisation
- ✓ Debit Card authorisation
- ✓ Paywave authorisation
- ✓ CompacPay mobile App



Compac Payment Terminals are built to last and are ideal for any Unattended Refuelling Site:



Marine



Commercial



Retail



Aviation

Compac Payment Terminals offer great versatility in their functionality. All Payment Terminals have the ability to connect to:

- ✓ Compac's **Payment App** for pump authorisation
- ✓ **CompacOnline** for fuel management
- ✓ Compac's **Automatic Vehicle Recognition** system

Compac's **PT1 v2 Payment Terminal** features also include:

- ✓ Online Account Card authorisation
- ✓ Credit Card authorisation
- ✓ Debit Card authorisation
- ✓ Paywave available



Easy to use and built from Stainless Steel, Compac Payment Terminals are robust and designed to withstand the harshest conditions.



PT1 v2 Payment Terminal Specifications

Model	PT1v2
Installation	IMPORTANT NOTE: The Compac PT1 Payment Terminal is NOT approved for installation in a Hazardous Area. It must be installed OUTSIDE the Hazardous Area
Display	Now with full colour 7" LCD touch screen Display featuring high visibility advanced graphics and video with 1024 x 600 resolution
Pinpad	Storm PINPad with long life metal keys
Card Reader	Windcave SCR200 Card Reader for EFTPOS and Credit Cards Outdoor, unattended, Magtek Card Reader for Account Cards Optional: Paywave reader, QR Code / Bar Code reader
Printer	Thermal printer specifically designed for outdoor unattended use with presenter designed to prevent jamming. Paper roll dimension 80mm wide x 295mm long
Authorisation	Account Cards with offline functionality All major Credit Cards Debit Cards Mobile Payment App Prepay Card Support QR Code / Barcode
Power Supply	200 - 240V, 3.4 amps UPS, battery backed, enables customers to get receipts in event of power failure Provides power and surge protection
Supported Fuel Pumps	Compac, Gallagher, Gilbarco, Wayne
Communications	4G / 5G or Ethernet
Operating Temperature	-25°C to 55°C with internal thermostat environmental control for optimal low temperature operation
Tank Gauging Interface	Colibri, Fafnir, Veeder-Root with 4-20ma probe (max 2)
Construction	Stainless Steel
Mounting Options	Wall, tank or pedestal



Compac Industries Ltd,
52 Walls Road, Penrose,
Auckland 1061.
New Zealand.

PO Box 12 417, Penrose,
Auckland 1642.
New Zealand.

Tel: +64 9 5792094

www.compac.co.nz

Compac Sales Pty Ltd,
32 Boundary St,
South Melbourne VIC 3205.
Australia.

PO Box 312 Port Melbourne,
VIC 3207.
Australia.

Tel: +61 3 8696 4802

Fax: +61 3 9682 1985

www.comsales.com.au

Compac Industries India Ltd,
K73 Udyog Nagar,
Main Rohtak Road.
Delhi - 110041.
India.

Mobile: +91 85888 78287

www.compacindia.com